characteristics ESD Nexxit 3 with glides and footring

Article: 9031E artificial leather

Dimensions in mm	Backrest:	H:	530
	Seat:	H:	570-820
		B:	460
		T:	400-460
Packing data	Weight	kg	20,5
	Volume	m³	0,175



Base equipment		Benefit
Conductivity	The metal components have a conductive coating The high-comfort upholstery is also conductive Typical discharge resistance of 10^6 Ohm Conductive castors.	Exceeds the requirements of ESD protection according to standard DIN EN 61340-5-1 100% ESD protection.
Backrest	Ergonomically shaped backrest with horizontal stitching, tapers upwards. Backrest height adjustment by 60 mm	Relieves the strain on the spine and muscles. Healthy sitting posture due to the wide support for the back around the lumbar vertebrae. Pleasant microclimate on the back and optimum freedom of movement for the arms.
Seating surface	Ergonomically shaped seating surface with chamfer integrated into the edge of the seat.	Ensures that people are ideally supported - especially around the lumbar vertebrae - no matter their size. Automatically requires the sitting posture to be correct. The chamfers prevent blood congestion in the thighs.
Upholstered Seat	Magic ESD Artificial Leather Washable, low maintenance, resistant to disinfectants, durable, soft and comfortable, PVC-free, phthalate-free, resistant to blood and urine, fire protection according to EN 1021 Part 1 + 2 Colour: Black.	The soft, comfortable upholstery provides good seating comfort. Washable and disinfectable. Free from plasticizers so lasting softness and comfort.
Functional handles	Stable and robust functional handles on the backrest. Available in the colour black (3218).	Maximum mobility and simple handling of the chair.
Base	5 star base made from steel shape tube, powder-coatet. Flat design.	Very high stability, longevity. Flat design prevents stumbling hazard.
Foot ring	Chromed height-adjustable foot ring.	Provides support thanks to the wide step area and the height can be adjusted simply and quickly.
Glides	Large and abrasion-resistant plastic floor gliders.	Excellent stability
Material	The material used is recyclable.	Environmentally friendly.

characteristics ESD Nexxit 3 with glides and footring

Article: 9031E artificial leather

Dimensions in mm	Backrest:	H:	530
	Seat:	H:	570-820
		B:	460
		T:	400-460
Packing data	Weight	kg	20,5
	Volume	m³	0,175



Technology Synchronous technology with automatic weight

adjustment, incl. manual precision adjustment

and angle limitation in three settings.

Seat inclination adjustment by 6°

Seat depth adjustment by 60 mm

Rapid adjustment

DIN 68 877

GS certificate for "tested safety"
DIN EN ISO 9001 quality management
DIN EN ISO 14001 environmental

management

EMAS tested environmental management OHSAS 18001 occupational health and

safety management

EcoVadis CSR rating 2015 Gold.

10-year long-term-guarantee - 3 years of which

full guarantee.

Ideal support which makes it possible to switch between various sitting postures at the same time. This enables dynamic sitting, relaxes the muscles, relieves the strain on the discs, improves blood flow and significantly increases concentration and performance. The backrest pressure is adapted automatically. Additional precision adjustment is possible. Several users can use the chair in alternation without having to constantly reset the weight adjustment.

Many tasks are performed in a posture which is slightly raised and angled forwards. A correspondingly inclined seating surface ensures a seating angle of at least 90° while contact with the backrest is maintained.

Adapts the depth of the seat to the body size and therefore provides an ideal surface for the thighs to rest on. Contact with the backrest and therefore its support is always retained.

All functions can be operated conveniently and simply while seated using the operating lever.

Verified by certificates from independent testing institutes, quality, environmental friendliness and procurement security.

Quality assured and cost effective. Exchange of parts, free of charge, within the guaranteed period.

Guarantee

Standards

characteristics ESD Nexxit 3 with glides and footring

Article: 9031E artificial leather

Dimensions in mm	Backrest:	H:	530
	Seat:	H:	570-820
		B:	460
		T:	400-460
Dooking data			00.5
Packing data	Weight	kg	20,5
	Volume	m³	0,175



Options		Benefit
Base A	Aluminium base polished.	High quality. Attractive design.
m in	Multifunctional armrest Height-adjustable (100 mm), width-adjustable (continuously by increments of 25 mm), depth-adjustable (50 mm), pivotable (30°), soft armrest pads.	The armrests relieve the neck muscles. The adjustment options guarantee the ideal position for all users.