characteristics ESD Basic 3 with glides and footrest

Article: 9156E fabric

Dimensions in mm	Backrest:	H:	530
	Seat:	H:	630-890
		B:	460
		T:	440
Packing data	Weight	kg	20,0
	Volume	m³	0,18



Base equipment		Benefit
Conductivity	The metal components have a conductive coating The high-comfort upholstery is also conductive Typical discharge resistance of 10^6 Ohm	Exceeds the requirements of ESD protection according to standard DIN EN 61340-5-1. 100% ESD protection.
Backrest	Conductive glides. Large, ergonomically designed backrest to take the strain off the spine and muscles with integrated lumbar support.	Healthy posture due to a hump providing support for the back in the lumbar region.
	Backrest height adjustment convenient and easy to handle in sitting position.	The support area can be adapted in accordance to the user's body size.
Seat	Ergonomically designed seat with rounded front edge.	The round front edge of the seat prevents blocked circulation in the thighs.
Finishes for seat and backrest	ESD fabric upholstery: Resistant, breathable and comfortable ESD-fabric Duotec Selectable in following colours: Black (9801) Blue (9802) Grey (9811) Red (9803)	This high-quality fabric upholstery is breathable and can both absorb and expel moisture. The extremely soft surface guarantees maximum comfort.
Seat height	Stepless seat height setting from 620 - 870 mm supported by safety gas spring with protective cover.	Seat height can be adapted to nearly 95 % of all body sizes, the cover protects the gas spring from dust and dirt.
Functions / Mechanism	Permanent contact backrest with additional seat inclination adjustment.	This mechanism ensures that the backrest responds immediately to any movements of the upper body by following them. Thus, the back remains supported all the time. The backrest can also be locked into any tilt position if required.
		There is a continuously variable mechanism for tilting the seat forwards. This ensures that your posture remains relaxed even when you need to bend forwards into your work. Less pressure is exerted on the thigh area, which encourages steady circulation. The problem of sitting all hunched up is masterfully avoided thanks to a mechanism that ensures a minimum angle of 90° between your legs and upper body at all times.
	Quick adjustment	Every function can be operated comfortable and easy in sitting position.
	Anti-Shock lock	The backrest cannot accidentally spring forwards even after the lock has been released.
Base	Black 5 star base made from steel shape tube, conductive, powder-coatet, black. Flat design.	Very high stability, longevity. Flat design prevents stumbling hazard.
Glides	Wearproof plastic glides with a large surface area, conductive.	Offer a superb level of stability.

characteristics ESD Basic 3 with glides and footrest

Article: 9156E fabric

Footrest

Dimensions in mm	Backrest:	H:	530
	Seat:	H:	630-890
		B:	460
		T:	440
Packing data	Weight	kg	20,0
	Volume	m³	0,18



Height adjustable footrest. Footrest adapts to height adjustment and rotation of the

seat.

Non-slip step.

Procuring is insured.

Materials Environmentally friendly. The materials used are recyclable.

Standards 100% ESD protection. DIN EN European standard 61340-5-1 for

ESD-protected areas

DIN 68 877 German GS "safety tested" mark

of confirmity

Quality Management System DIN EN ISO

9001

Regulation EWG Nr. 1836/93 and

Warranty 10 year long term warranty, 3 years full Guaranteed quality and high efficiency. warranty.

characteristics ESD Basic 3 with glides and footrest

Article: 9156E fabric

Dimensions in mm	Backrest:	H:	530
	Seat:	H:	630-890
		B:	460
		T:	440
Packing data	Weight	kg	20,0
	Volume	m³	0,18



Options		Benefit
Armrests	Loop armrests	Made of polyamide, adjustable in width (20 mm).
	Multifunctional armrest ESD	The armrests are adjustable in height, width and depth to suit the individual user. Further, they are conductive.
Accessories	Foot ring	The foot ring can be retrofitted by attaching it to the chair column
Options	ESD plus option	With volume conductive plastic parts and frame
	Light grey frame	
	Polished aluminium base	