

### characteristics ESD Stool 3 with glides and footring

Article: 9461E integral foam

Dimensions in mm

Seat:	H:	560 - 830
	B:	400
	T:	400

Packing data	Weight	kg	8,92
	Volume	m <sup>3</sup>	0,09



#### Base equipment

		Benefit
Conductivity	Steel parts with a conductive coating Comfortable, conductive upholstery Typical leakage resistance of 10 <sup>6</sup> ohm Volume-conductive castors	Exceeds the ESD requirements of DIN EN 61340-5-1. Complete ESD safety.
Seat	Extra-large seat with a diameter of 400 mm. Extra-strong and soft 60 mm comfort upholstery.	Automatically encourages a correct sitting posture and upright, healthy sitting. The rounded front edge of the seat prevents possible blood congestion in the thighs.
Upholstery protection	Upholstery protection underneath the seat	Protects the upholstery from edges and corners.
Seat design	Integral foam upholstery (PU): The integral foam pad offers maximum resistance and ease of cleaning. Extremely robust, durable, washable, disinfectant-proof, PVC-free, resistant to blood and urine, fire protection in accordance with EN 1021 Parts 1 + 2, black colour.	Recommended use in environments where staff come into contact with aggressive working materials. The surface is resistant, extremely robust, washable and easy to clean. Resistant to pointed and sharp objects.
Seat height	Infinitely variable seat height adjustment from 560-830 mm by gas spring with protective cover.	Large seat height adjustment range. The cover protects the gas spring against dust and dirt.
Technology	Ring release	Easy and convenient height adjustment from any sitting position thanks to a ring release underneath the seat.
Base	Particularly small aluminium base with a diameter of 54 cm.	Space-saving and high mobility due to the available legroom.
Castors/glides	Wearproof plastic glides with a large surface area.	Offer a superb level of stability
Foot ring	Height adjustable, chrome-plated foot ring.	Wide foot plate provides good support. Height can be quickly and easily adjusted.
Material used	All materials can be recycled separately.	Environmentally friendly

**characteristics ESD Stool 3 with glides and footing**

Article: 9461E integral foam

Dimensions in mm

Seat:	H:	560 - 830
	B:	400
	T:	400

Packing data	Weight	kg	8,92
	Volume	m <sup>3</sup>	0,09



Standards

DIN 68 877  
 DIN EN 61340-5-1  
 GS certificate for "tested safety"  
 DIN EN ISO 9001 quality management  
 DIN EN ISO 14001 environmental management  
 EMAS tested environmental management  
 OHSAS 45001 occupational health and safety management  
 EcoVadis CSR rating 20 Gold

Procurement security

Warranty

10-year long-term warranty, with 3-year full warranty

Free shipping of replacement parts within the entire period.

**characteristics ESD Stool 3 with glides and footring**

Article: 9461E integral foam

Dimensions in mm

Seat:	H:	560 - 830
	B:	400
	T:	400

Packing data	Weight	kg	8,92
	Volume	m <sup>3</sup>	0,09



**Options**

ESD Flex support	ESD Flex support, height adjustable by 100 mm
------------------	---

**Benefit**

The ESD-compliant Flex support acts both as an armrest and as a backrest. It represents a simple upgrade and turns the stool into a flexible, compact and yet comfortable seating solution. Easy to clean and pleasantly soft.