

characteristics ESD Stool 3 with glides and footing

Article: 9461E Supertec

Dimensions in mm

| | | |
|-------|----|-----------|
| Seat: | H: | 560 - 830 |
| | B: | 400 |
| | T: | 400 |

| | | | |
|--------------|--------|----------------|------|
| Packing data | Weight | kg | 8,92 |
| | Volume | m ³ | 0,09 |



| Base equipment | | Benefit |
|-----------------------|---|---|
| Conductivity | Steel parts with a conductive coating Comfortable, conductive upholstery Typical leakage resistance of 10 ⁶ ohm Volume-conductive castors | Exceeds the ESD requirements of DIN EN 61340-5-1. Complete ESD safety. |
| Seat | Extra-large seat with a diameter of 400 mm. Extra-strong and soft 60 mm comfort upholstery. | Automatically encourages a correct sitting posture and upright, healthy sitting. The rounded front edge of the seat prevents possible blood congestion in the thighs. |
| Upholstery protection | Upholstery protection underneath the seat | Protects the upholstery from edges and corners. |
| Seat design | Supertec (global innovation): Comfortable, soft, breathable and extremely resistant. Cut-resistant, non-slip and easy to clean. Fire protection in accordance with EN 1021 Part 1, black colour. | The new cover material for comfortable and robust workplace chairs and stools in production. Provides excellent seating comfort thanks to the breathable fabric underlayer. Resistant to damage caused by sharp objects thanks to the micro-plating on the surface. |
| Seat height | Infinitely variable seat height adjustment from 560-830 mm by gas spring with protective cover. | Large seat height adjustment range. The cover protects the gas spring against dust and dirt. |
| Technology | Ring release | Easy and convenient height adjustment from any sitting position thanks to a ring release underneath the seat. |
| Base | Particularly small aluminium base with a diameter of 54 cm. | Space-saving and high mobility due to the available legroom. |
| Castors/glides | Wearproof plastic glides with a large surface area. | Offer a superb level of stability |
| Foot ring | Height adjustable, chrome-plated foot ring. | Wide foot plate provides good support. Height can be quickly and easily adjusted. |
| Material used | All materials can be recycled separately. | Environmentally friendly |
| Standards | DIN 68 877 DIN EN 61340-5-1 GS certificate for "tested safety" DIN EN ISO 9001 quality management DIN EN ISO 14001 environmental management EMAS tested environmental management OHSAS 45001 occupational health and safety management EcoVadis CSR rating 20 Gold | Procurement security |

characteristics ESD Stool 3 with glides and footring

Article: 9461E Supertec

Dimensions in mm

| | | |
|-------|----|-----------|
| Seat: | H: | 560 - 830 |
| | B: | 400 |
| | T: | 400 |

Packing data

| | | |
|--------|----------------|------|
| Weight | kg | 8,92 |
| Volume | m ³ | 0,09 |



Warranty

10-year long-term warranty, with 3-year full warranty

Free shipping of replacement parts within the entire period.

characteristics ESD Stool 3 with glides and footring

Article: 9461E Supertec

Dimensions in mm

| | | |
|-------|----|-----------|
| Seat: | H: | 560 - 830 |
| | B: | 400 |
| | T: | 400 |

Packing data

| | | |
|--------|----------------|------|
| Weight | kg | 8,92 |
| Volume | m ³ | 0,09 |



Options

ESD Flex support

ESD Flex support, height adjustable by 100 mm

Benefit

The ESD-compliant Flex support acts both as an armrest and as a backrest. It represents a simple upgrade and turns the stool into a flexible, compact and yet comfortable seating solution. Easy to clean and pleasantly soft.