

## characteristics ESD Stool 2 with castors

Article: 9463E artificial leather

Dimensions in mm

Packing data

Seat: H: 450 - 650 B: 400

B: 400 T: 400

 $\begin{array}{ccc} \text{Weight} & \text{kg} & 7,56 \\ \text{Volume} & \text{m}^{\text{3}} & 0,09 \\ \end{array}$ 



Base equipment		Benefit
Conductivity	Steel parts with a conductive coating Comfortable, conductive upholstery Typical leakage resistance of 10 <sup>A</sup> 6 ohm Volume-conductive castors	Exceeds the ESD requirements of DIN EN 61340-5-1. Complete ESD safety.
Seat	Extra-large seat with a diameter of 400 mm. Extra-strong and soft 60 mm comfort upholstery.	Automatically encourages a correct sitting posture and upright, healthy sitting. The rounded front edge of the seat prevents possible blood congestion in the thighs.
Upholstery protection	Upholstery protection underneath the seat	Protects the upholstery from edges and corners.
Seat design	Magic synthetic leather upholstery: Washable, easy-care, disinfectant-proof, soft and comfortable, PVC-free, phthalate-free, resistant to blood and urine. Fire protection in accordance with EN 1021 Part 1 + 2. Colour: Black.	The soft and comfortable upholstery offers excellent sitting comfort. Easy to clean, can be washed and disinfected. Free of softeners and therefore soft and comfortable even after years of use.
Seat height	Infinitely variable seat height adjustment from 450-650 mm by gas spring with protective cover.	Large seat height adjustment range. The cover protects the gas spring against dust and dirt.
Technology	Ring release	Easy and convenient height adjustment from any sitting position thanks to a ring release underneath the seat.
Base	Particularly small aluminium base with a diameter of 54 cm.	Space-saving and high mobility due to the available legroom.
Castors/glides	Load-dependent braked and soft double castors for hard floors.	Stools are braked when not used which decreases the risk of accidents.
Material used	All materials can be recycled separately.	Environmentally friendly
Standards	DIN 68 877 DIN EN 61340-5-1 GS certificate for "tested safety" DIN EN ISO 9001 quality management DIN EN ISO 14001 environmental management EMAS tested environmental management OHSAS 45001 occupational health and safety management EcoVadis CSR rating 20 Gold	Procurement security
Warranty	Ecovadis CSR rating 20 Gold  10-year long-term warranty, with 3-year full warranty	Free shipping of replacement parts within the entire period.

Hocker



## characteristics ESD Stool 2 with castors

Article: 9463E artificial leather

Dimensions in mm

 Seat:
 H:
 450 - 650

 B:
 400

 T:
 400

 Packing data
 Weight kg 7,56

 Volume m³ 0,09





## characteristics ESD Stool 2 with castors

Article: 9463E artificial leather

Dimensions in mm

| Seat: H: 450 - 650 |
| B: 400 |
| T: 400 |
| Packing data | Weight kg 7,56 |
| Volume m³ 0,09



Options		Benefit
ESD Flex support	ESD Flex support, height adjustable by 100 mm	The ESD-compliant Flex support acts both as an armrest and as a backrest. It represents a simple upgrade and turns the stool into a flexible, compact and yet comfortable seating solution. Easy to clean and pleasantly soft.