bimos

characteristics ESD Stool 2 with castors

Article: 9463E integral foam

Dimensions in mm

	Seat:	H:	450 - 650
		B:	400
		T:	400
Packing data	Weight	kg	7,56
	Volume	m³	0,09

ą	Ĩ	
	I	đ

Base equipment		Benefit
Conductivity	Steel parts with a conductive coating Comfortable, conductive upholstery Typical leakage resistance of 10 ⁶ ohm Volume-conductive castors	Exceeds the ESD requirements of DIN EN 61340-5-1. Complete ESD safety.
Seat	Extra-large seat with a diameter of 400 mm. Extra-strong and soft 60 mm comfort upholstery.	Automatically encourages a correct sitting posture and upright, healthy sitting. The rounded front edge of the seat prevents possible blood congestion in the thighs.
Jpholstery protection	Upholstery protection underneath the seat	Protects the upholstery from edges and corners.
Seat design	Integral foam upholstery (PU): The integral foam pad offers maximum resistance and ease of cleaning. Extremely robust, durable, washable, disinfectant-proof, PVC-free, resistant to blood and urine, fire protection in accordance with EN 1021 Parts 1 + 2, black colour.	Recommended use in environments where staff come into contact with aggressive working materials. The surface is resistant, extremely robust, washable and easy to clean. Resistant to pointed and sharp objects.
Seat height	Infinitely variable seat height adjustment from 450-650 mm by gas spring with protective cover.	Large seat height adjustment range. The cover protects the gas spring against dust and dirt.
Fechnology	Ring release	Easy and convenient height adjustment from any sitting position thanks to a ring release underneath the seat.
Base	Particularly small aluminium base with a diameter of 54 cm.	Space-saving and high mobility due to the available legroom.
Castors/glides	Load-dependent braked and soft double castors for hard floors.	Stools are braked when not used which decreases the risk of accidents.
Naterial used	All materials can be recycled separately.	Environmentally friendly
Standards	DIN 68 877 DIN EN 61340-5-1 GS certificate for "tested safety" DIN EN ISO 9001 quality management DIN EN ISO 14001 environmental management EMAS tested environmental management OHSAS 45001 occupational health and safety management	Procurement security

bimos

characteristics ESD Stool 2 with castors

Article: 9463E integral foam

Dimensions in mm

	Seat:	H:	450 - 650
		B:	400
		T:	400
Packing data	Weight Volume	kg m³	7,56 0,09



Warranty

10-year long-term warranty, with 3-year full warranty

.

Free shipping of replacement parts within the entire period.

.....

bimos

characteristics ESD Stool 2 with castors

Article: 9463E integral foam

Dimensions in mm

	Seat:	H:	450 - 650
		B:	400
		T:	400
Packing data	Weight	kg	7,56
	Volume	m³	0,09



Benefit

Options

ESD Flex support

ESD Flex support, height adjustable by 100 mm

The ESD-compliant Flex support acts both as an armrest and as a backrest. It represents a simple upgrade and turns the stool into a flexible, compact and yet comfortable seating solution. Easy to clean and pleasantly soft.